

Solderless Field Termination Captive Pin N Connectors

SKU: 970024

MSRP: \$14.95

Product Web Page:





Connector Body

FEATURES

- The gold-plated captive center pin allows the cable to be terminated without soldering or crimping.
- The solderless N connectors are meant to terminate LMR400 or equivalent cable (connectors will work on Wilson-400, LMR-400, CNT-400, TWS-400).
- The connector is fabricated with nickel plated brass and is acceptable for indoor or outdoor use.
- The connectors can only be used on cables with a solid conductor.
- Marning: Cancer and Reproductive Harm www.P65Warnings.ca.gov

About

The solderless connectors can be used to field terminate cables. The connectors eliminate soldering, which makes it easier to get a good termination while on location. This allows installers to make custom cable lengths in the field rather than having to measure cable runs before the installation and building cables in the shop of the job.

ELECTRICAL

Supported Frequencies	0~3.0 GHz
Impedance	50 Ω
VSWR	\leq 1.18 at 0~3.0 GHz
Withstanding Voltage	≥1500V

Kit Includes



Connector Body Clamp Bushing

Insulator & Shrink Boot



Package Dimensions

Sealed Polybag 3.0" L x 5.5" W



MASTER CARTON (50 QTY.): 16 L x 12 W x 6 H I 5.88 lbs.

FOR PARTNER'S USE

Support



Email: support@wilsonelectronics.com **Website:** http://support.weboost.com

Phone: +1 866 294 1660 Monday to Saturday

UPC

