



Overview

Presentation	Deep Universal IT Enclosure for low to medium density server and networking applications that either require additional equipment clearance space or more open space for ease of access in the rear of the enclosure. Compact width to optimize data center space. 42U height to easily roll through doorways.
Lead time	Usually in Stock

Main

Product or Component Type	Rack enclosure
Number of rack unit	42U
Provided equipment	Baying hardware Doors Key(S) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters 4 x Bolt down brackets Roof Side Panels Unpacking sheet

Physical

Height	81.0 in (205.7 cm)
Width	23.6 in (60 cm)
Depth	47.2 in (120 cm)
Net Weight	267.42 lb(US) (121.3 kg)
Color	Black
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Mounting position	Vertical
Maximum Mounting Depth	36.10 in (91.69 cm)
Minimum mounting depth	6.60 in (16.76 cm)
Rack width	19"
Marking	14 gauge EIA mounting rail 16 gauge front door 18 gauge post 16 gauge rear door 19 gauge roof 18 gauge side panels
Permanent permissible load	1014 Lb(US) (459.94 kg) dynamic 2205 lb(US) (1000.17 kg) static

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------






Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304302094
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	85.9 in (218.1 cm)
Package 1 Width	27.6 in (70 cm)
Package 1 Length	51.2 in (130 cm)
Package 1 Weight	307.999 lb(US) (139.706 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------