



Product: [KEYCONNECT SIDE ENTRY BOXES](#) 

KeyConnect Side-Entry Box, 6, 4, 2, or 1-Port

Product Description

KeyConnect Side-Entry Box. Available in several colors and port counts.

Technical Specifications

Product Overview

Suitable Applications:	Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400 and 1200.
------------------------	--

Physical Characteristics (Overall)

Height:	1.8 m
Width:	2.56
Depth:	1.2
Front Connection:	Flush
Packaging:	Individually packaged in a plastic bag.
Weight:	0.07 kg

Connectors

Materials

Material
Plastic - UL94V-0

Temperature Range

Installation Temp Range:	-10 to 60°C
Storage Temp Range:	-40 to 70°C
Operating Temp Range:	-10 to 60°C

Mechanical Characteristics

Footprint/Type:	KeyConnect
-----------------	------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL2043 Air Handling Spaces
Safety Listing:	Bi-national Standard Listed

Related Part Numbers

Related Parts:	Recommended to be used with REVConnect and KeyConnect Modular Jacks
----------------	---

Variants

Item #	Color	Port Count
--------	-------	------------

AX104132	Almond	1 Port
AX104133	Almond	2 Port
AX104134	Almond	4 Port
AX104135	Almond	6 Port
AX105352-AL	Almond	1 Port
AX105353-AL	Almond	2 Port
AX105354-AL	Almond	4 Port
AX105355-AL	Almond	6 Port
AX105352-BK	Black	1 Port
AX105353-BK	Black	2 Port
AX105352-GS	Dark Gray	1 Port
AX102651	Electric White	1 Port
AX102652	Electric White	2 Port
AX102653	Electric White	4 Port
AX102654	Electric White	6 Port
AX105352-EW	Electric White	1 Port
AX105354-EW	Electric White	4 Port
AX105355-EW	Electric White	6 Port

Product Notes

Included Parts:	clear window, label, screws, cable tie, adhesive foam pad, color icon, instruction sheet
-----------------	--

History

Update and Revision:	Revision Number: 0.178 Revision Date: 12-15-2021
----------------------	--

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.