Securitron[®] CEPT Concealed Electrical Power Transfer

Experience a safer and more open world

The heavy-duty, tamper-resistant Concealed Electrical Power Transfer (CEPT) securely transfers power and data from the hinge side of the frame to electrified hardware on the door.

Aesthetically Pleasing

- Concealed wiring pathway when mortised into door and frame above second hinge
- Available in four architectural finishes
- Direct replacement for competitive product with the same prep

Tested for Durability

- ANSI/SDI-BHMA A250.13 (+/- 150 psi) Windstorm Listed and Florida Building Code Approved
- ANSI/UL 10C Listed, 3 hour rated and ULC-S318 Listed, 3 hour rated
- Tested to 1,000,000 cycles

Robust Design

- All stainless steel construction no plastic parts
- Tamper resistant with no exposed openings to allow foreign objects to reach wires or jam the device







Secure | Concealed | Durable

Specifications

Certifications

- ANSI/UL 10C Listed, 3 hour rated
- ULC-S318 Listed, 3 hour rated
 ANSI/SDI-BHMA A250.13
- (+/- 150 psi) Windstorm Listed
- Florida Building Code Approved

Dimensions

 CEPT Housing: 9-1/16"L x 1-3/16"W x 1-7/16"D [230.2mm L x 30.12mm W x 36.52mm D]

Shipping Weight

2.40 lbs [1.09kg]

Features

Standard Features

- Mortises into the edges of the door and frame
- Direct retrofit for competitor products
- Tamper resistant
- All metal construction including back boxes
- 7/8" [22.25mm] knockouts on back boxes accommodate EMF-type fittings
- Tested to 1 million cycles
- Compatible with butt hinges up to 6" [152.4mm] and continuous hinges with cutout
- MagnaCare[®] lifetime replacement, no-fault, no questions asked warranty

Optional Features

- CEPT-10 includes 8–22 AWG wires plus 2–18 AWG wires for higher current devices
- CEPT-C5E includes CAT5E compatible with 8-24 AWG wires, 1–22 AWG wire, conductor, Molex connectors
- EL-CEPT is ElectroLynx[®] compatible with 12-22 AWG wires, ElectroLynx connectors

Dimensions





0

0

1.03"

[26mm]

Technical note

- Not for use with center hung or balanced doors, pocket or offset pivots or swing clear hinges.
- Door swing ranges when installed with butt hinges are:

Hinge Size Door	Swing Range
5" [127mm] or less	up to 180
5-1/2" [139.7mm]	up to 130
6" [152.4mm] Butt Hinge	up to 110

How to Order

Wire Connectors	Shape	Number of Wires	Finish
EL	– CEPT	– C5E	– 10B
(blank) No Connectors	CEPT Concealed	(blank) 12 Wires	(blank) 630 Satin Stainless finish
EL Electrolynx Connectors		10 10 Wires	04 606 Satin Brass finish
		C5E 9 Wires	10 612 Satin Bronze finish
			10B 613 Oil Rubbed Bronze finish

ELECTRONIC SECURITY HARDWARE HES | Securitron

assaabloyesh.com **800 626 7590 |** 10027 S. 51st Street, Ste. 102 Phoenix, AZ 85044 USA Patent pending and/or patent www.assaabloydss.com/patents

Copyright © 2019, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Hanchett Entry Systems, Inc. is prohibited. ESH-SEC-30-0819