




# CX-ED1410 'ANSI' GRADE 1 FIRE ELECTRIC STRIKE

## DOOR FRAME TYPES



## COMPATIBLE LOCKSETS



## SPECIFICATIONS

VOLTAGE:	12/24V AC/DC
CURRENT DRAW:	260MA@12V AC/DC 150MA@24V AC/DC
STATIC HOLD FORCE:	1,500 LBS.
DYNAMIC STRENGTH:	70 FT-LBS.
ENDURANCE:	1,000,000 CYCLES (FACTORY TESTED) 250,000 CYCLES (UL VERIFIED)
FIRE RATING:	90 MINUTES (UL VERIFIED)
LATCH PROJECTION:	5/8" - 3/4" (16mm - 19mm)
MODE:	FIELD SELECTABLE FAIL SAFE/FAIL SECURE (FIRE RATED IN FAIL SECURE MODE ONLY)
OPERATION:	AC – BUZZ, DC – SILENT
DUTY:	CONTINUOUS
DIMENSIONS (BODY):	3 3/8"L x 1 7/8"W x 1 3/8"D (86mm x 47mm x 35mm)

## ORDERING INFORMATION

CX-ED1410: GRADE 1 'ANSI' FIRE ELECTRIC STRIKE, 12/24V AC/DC, FAIL SAFE/FAIL SECURE OPERATION

## CUTTING JIG

CX-JIG3: JIG FOR INSTALLING ANSI STRIKES WITH 3/4" LATCH



CX-JIG3