



Product: [FX UHD Cassette OM4 06P Splice](#)

FX UHD Splice Cassette OM4 6 Ports

Product Description

FX UHD Splice Cassette OM4 6 Ports. Available in several fiber connector types and adapter colors.

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers

Construction

Fiber Cable Construction

Fiber Type	
OM4	
Weight:	0.657 lbs
Height:	1.5 m
Width:	4.5
Length:	6.6 ft

Mechanical Characteristics

Front Connection:	Static
-------------------	--------

Temperature Range

Operating Temp Range:	-10 to 60°C
Storage Temp Range:	-10 to 75°C

Product Material

Materials

Element	Description	Material	Color
Zirconia-Ceramic	Adapter Sleeve Material	Zirconia-Ceramic	
Plastic - UL94V-0	Front Connector Body	Plastic - UL94V-0	Erika Violet
Plastic - UL94V-0	Cassette Assembly	Plastic - UL94V-0	Black

Standards

MII Order #39 (China RoHS):	EUP 50
-----------------------------	--------

Part Number

Related Parts:	FX UHD & FXU Patch Panels, FX MPO Trunks
----------------	--

Variants

Item #	Color	Connector Type
FC4H06SDFS	Erika Violet	SC Duplex
FC4H06LKFSNY	Erika Violet	LC Keyed Yellow
FC4H06LKFSNW	Erika Violet	LC Keyed White

FC4H06LKFSNV	Erika Violet	LC Keyed Violet
FC4H06LKFSNS	Erika Violet	LC Keyed Gray
FC4H06LKFSNR	Erika Violet	LC Keyed Red
FC4H06LKFSNP	Erika Violet	LC Keyed Rose
FC4H06LKFSNO	Erika Violet	LC Keyed Orange
FC4H06LKFSNN	Erika Violet	LC Keyed Black
FC4H06LKFSNM	Erika Violet	LC Keyed Brown
FC4H06LKFSNG	Erika Violet	LC Keyed Green
FC4H06LKFSNB	Erika Violet	LC Keyed Blue
FC4H06LKFSNA	Erika Violet	LC Keyed Aqua
FC4H06LDFS	Erika Violet	LC Duplex

Product Notes

Packaging:	Individually packaged in a plastic shell, Shipped in cardboard box (14/box)
------------	---

History

Update and Revision:	Revision Number: 0.47 Revision Date: 03-17-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.