

iBridge Video™: Affordable Professional Hi-Res. Remote Video



Outdoor Dome with POE option

WiFi Doorbell, 1080P Pro Grade w/ night vision & noise-cancellation.

High HD resolution remote video online or on a smart device up to 20 frames per second at HD res (1280 x 960).



2 Apps: Standalone or Integrated System



- New! Professional Video Doorbell: for New & Existing Systems:**
- Professional grade 1080HD video, two-way audio, customizable motion sensors & top IP65 ingress rating**
- ✓ HD Video with two-way talk & noise-cancellation
 - ✓ Custom PIR motion zones
 - ✓ Day & Night Live-View & archived video with infrared night vision
- **Sends instant alerts to accounts when visitors press the doorbell or trigger the built-in motion sensors**, so they can hear and speak to anyone at the door from any smartphone, tablet or PC.
 - Motion-activated alerts
 - Video on Demand with Live-View
 - Simple 3-button operation - Buttons appear on smartphone screen over video - Press "Accept" to talk (2-way chat), or "Hang up" to disconnect, or "Mute" to just watch
 - Durable & weather-resistant, IP-65 Rated (from -4 to 122°F)
 - Slim 4.7" x 1.9" x 1.1" iBridge Video Doorbell fits virtually anywhere
 - Smart PIR motion detection w/ 3 configurable zones, broad 140° FOV
 - Doorbell is easily enrolled and appears like any other WiFi iBridge Video Camera in the full integrated iBridge Connected Home or Standalone iBridge Video ecosystem, uses free Apps on iTunes®/Google Play®
 - 12-mos. cloud-storage plan included (time-/date-stamped archive)
 - Uses existing doorbell power & wiring, with quick 2-wire AC installation
 - Over the Air (OTA) automatic firmware updates
 - Free Consumer Mailers/Statement Stuffers

iBridge Video™: Wi-Fi IP Indoor & Outdoor Cameras - Use alone or integrate with iBridge Connected Home App

WiFi Camera Features:

- Put video accounts online in as little as 10 minutes
- **Upsell your residential & small business alarm accounts on very affordable video for incremental RMR**
- High HD resolution remote video up to 20 frames per second at HD res (1280 x 960)
- **Built in 32GB Onboard HD video storage**, for up to 7 days, viewable from App or online.
- Choice of new cameras, including outdoor dome model, all including one year of cloud-based storage.
- **New outdoor dome camera with choice of WiFi or POE connectivity and mounting options** for wall, ceiling or eave. Ingress protection & vandal resistance, IP67, IK10.
- No dedicated wireless access point required
- Easiest 802.11 camera enrollment: Scan QR code, name camera and enroll in seconds
- **Free Apps** for standalone remote video or as part of iBridge Connected Home (including integral review of optional IVR archived video) on iTunes® and GooglePlay®
- Cameras support full duplex, **2-way audio through App - Talk to premises live** (excludes outdoor dome camera model).



Easy remote video app for use on smart devices or online, lets accounts see what they're missing.



iBridge Video™ Wi-Fi IP Indoor & Outdoor Remote Video



| | WiFi Fixed Camera | WiFi P/T Camera | WiFi Mini Dome Camera | WiFi Video Doorbell |
|---|---|---|---|---|
| Model | ISV2-CAM | ISV2-PT | ISV2-DOME | IBV-DBELL |
| WiFi | 2.4GHz | 2.4GHz | 2.4GHz | 2.4GHz |
| Hi-Def. Image Sensor | 1/3" 1.3MP CMOS | 1/3" 1.3MP CMOS | 1/3" 1.3MP CMOS | 1/2.7" 2MP CMOS |
| App for Standalone Remote Video | <i>iBridge® Video App</i> (iTunes®/GooglePlay®) | <i>iBridge® Video App</i> (iTunes®/GooglePlay®) | <i>iBridge® Video App</i> (iTunes®/GooglePlay®) | <i>iBridge Video App</i> (Standalone) |
| App for Integrated Video as a part of Connected Home | <i>iBridge® App</i> (iTunes®/GooglePlay®) | <i>iBridge® App</i> (iTunes®/GooglePlay®) | <i>iBridge® App</i> (iTunes®/GooglePlay®) | <i>iBridge® App</i> (integrated) (iTunes®/GooglePlay®) Soon! Live-View on iBridge Touch Touchscreen |
| iBridge Messenger, Video Notifications, MMS | MMS live pre/post video clips sent as Push Notifications to account | MMS live pre/post video clips sent as Push Notifications to account | MMS live pre/post video clips sent as Push Notifications to account | Push Notifications sent to account; live view & 3-button on-screen operation; video stored to cloud |
| Special Features | PIR w/ 19.7' Range | | PoE-Ready | IP65 Rated; PIR, aimable |
| Lens | 2.8mm/F2.2 | 3.6mm/F2.1 | 2.8mm/F2.0 | 1.9mm |
| FOV-H (Field of View) | 92° | 72° | 92° | 140° |
| Day/Night | Auto ICR | Auto ICR | DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC | Auto ICR & Infrared Night Vision |
| Wide Dynamic Range | DWDR | DWDR | DWDR | DWDR |
| Night Vision, Max IR Distance | 32.8' (10m) | 32.8' (10m) | 98.4' (30m) | 16.4' (5m) |
| Video Compression | H.264 | H.264 | H.264 | H.264 |
| Max. Resolution | 1.3MP (1280x960) | 1.3MP (1280x960) | 1.3MP (1280x960) | 2MP (1920x1080) |
| Frame Rate, Max. | 25/30fps@1.3MP | 30fps@1.3MP | 30fps@1.3MP | 20fps@2.0MP |
| Multi-streaming | 2 Streams | 2 Streams | 2 Streams | 2 Streams |
| Pan/Tilt/Rotation | Pan 0° -360°; Tilt 0°, 90°; Rotation 0-360° (fixed) | Pan 0°-355°; Tilt 0°- 90° | Pan 0° -355°; Tilt 0°- 90° (fixed) | n/a |
| Pan/Tilt/Range | n/a | Pan 0° -355°; Tilt 0°- 90°; 25 preset | n/a | n/a |
| Audio In/Out, 2-Way thru App | True 2-Way, Built in Mic/Speaker | True 2-Way, Built in Mic/Speaker | n/a | 2-Way Built in Omnidirectional Mic/Speaker w/ noise-cancellation |
| 7 Day Memory, Onboard | 32GB | 32GB | 32GB | use up to 64GB (optional) |
| Cloud Storage | 12mos., incldd | 12mos., incldd | 12mos., incldd | 12mos., incldd |
| Color | White/Gray | White/Smoke | White/Clear | Dark Metallic Gray |
| Mounting (std hardware incld) | Shelf/Wall | Shelf/Wall | Wall/Ceiling/Eave | Surface |
| Optional Mounting Accessories | | | Bracket ISV2-DOME BKT; Round Waterproof Junction Box ISV2-DOMEBOX | |
| Other Available Accessories | | | 4-Port PoE Switch, ISV2-POE-4P | |
| Compliances | CE, UL, FCC | CE, UL, FCC | CE, UL, FCC; IP67, IK10 | CE, UL, FCC |
| Operating Temperature | 14° ~ 113°F, Less than 95%RH | 14° ~ 113°F, Less than 95%RH | (-10)°C~ 122°F, Less than 95%RH | -4° to 122°F, Less than 95%RH |
| Dimensions, max. | 5"H x 3"W x 3.25" | 3.7" X 3.7" x 3.7" | 4.33" x 3.19" | 4.7" x 1.9" x 1.1" |
| Power Supply, included | DC 12V | DC 5V2A | DC 12V | 16-24V AC (optional 12/24 VDC from alarm system or standard power supply, not incld) |
| Weight | 5.5 oz | 7.76 oz | 1.2 lbs | 0.7 lbs |

Ordering Information for iBridge Video Wireless Cameras & Accessories

ISV2CAM WiFi Hi-Def. Fixed Camera with built-in PIR, true 2-way audio built in mic/speaker and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, fast-connect, up to 20/30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Gray styling, Shelf or wall mount. 5x 3 x 3.25" Includes power supply and mounting hardware. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. cloud-based storage. (Supports all current wireless routers - no special WAP required.)

ISV2-PT WiFi Hi-Def. Pan/Tilt Camera, true 2-way audio built in mic/speaker and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, fast-connect, up to 30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor; Pan 0-355 degrees and Tilt 0-90 degrees. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Smoke styling, Shelf or wall mount. 3.7 x 3.7 x 3.7". Includes power supply and mounting hardware. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. cloud-based storage. (Supports all current wireless routers - no special WAP required.)

ISV2-DOME WiFi Hi-Def. Indoor/Outdoor Dome Camera with POE option and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, Ingress & Vandal-Protected Weatherproof camera (IP67, IK10) for wall, ceiling or eave mounting. Professional grade, fast-connect, up to 30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Clear styling 4.33 x 3.19". Includes power supply and mounting hardware. Also see optional Mounting Bracket and Round Waterproof Junction Box and optional 4- or 8-Port PoE Switch. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. cloud-based storage. (Supports all current wireless routers - no special WAP required.)

ISV2-DM MTB Optional Round Junction Box for Dome Camera

ISV2-DM BKT Optional Wall Mounting Bracket for Dome Camera

ISV2-POE-4P 4 Port PoE Switch, optional accessory for dome camera, above. Two-layer industrial POE switch, MAC auto study and aging, MAC address list capacity is 8K. Support IEEE802.3af, IEEE802.3af standard.

ISV2-POE-8P 8 Port PoE Switch, optional accessory for ISV2-DOME camera, as above, but includes 8 ports.

IBV-DBELL WiFi Video Doorbell Professional grade 1080HD video, 2-way audio w/ noise cancellation, custom PIR zones, Day & Night Live View & archived video with infrared night vision. Subscribers enjoy easy 3-button operation, push notifications & archived video. Slimline design, top IP65 weather-rated, dark metallic gray, built in multidirectional mic/speaker, simply uses existing door bell power & 2-wire wiring. Full mounting hardware and 12-mos cloud video storage included.

IBR-TOUCH (option) Integrated Touchscreen, Video-View & Security System Control for Napco, Honeywell/ ADT® & DSC® Systems



A731 Free Enduser iBridge Video Doorbell Residential Mailers/Stuffers (right)



NAPCO, Amityville, NY | 1.800.645.9445 • www.napcosecurity.com

iBridge, iBridge Messenger and iBridge Video are trademarks of Napco. iTunes, Google Play and others are trademarks of their respective companies. ©NAPCO Security Technologies Inc. A696A 2019.6