



Model TS-27

Mushroom Push Button

Specifications

- Momentary action switch
- One normally-open and normally-closed contact rated at 10A at 35 VDC or 120 VAC
- Switch depth behind plate: 2-1/2"
- Operating temperature: -13 to +158F [-25 to +70C]
- UL 294 listed and CSA certified

Options

- Order TS-27R for red mushroom push button
- Order TS-27B for black mushroom push button

Models

TS-27

1-1/2" Diameter Green Push Button, 1 N/O, 1 N/C Momentary Switch, Continuous Contacts Rated 10 AMP "PUSH TO EXIT", 1-3/4" Stainless Steel Plate

TS-27B

1-1/2" Diameter Black Push Button, 1 N/O, 1 N/C Momentary Switch, Continuous Contacts Rated 10A, "PUSH TO EXIT", 1-3/4" Stainless Steel Plate

TS-27R

1-1/2" Diameter Red Push Button, 1 N/O, 1 N/C Momentary Switch, Continuous Contacts Rated 10A, "PUSH TO EXIT", 1-3/4" Stainless Steel Plate

Features

- Switch mounted on 1-3/4" 302 stainless steel wall plate
- Standard mushroom push button is green.
- Labeled "PUSH TO EXIT"
- Switch terminated with screw terminals

ALARMCONTROLS



ASSA ABLOY