

TS-7T INSTALLATION INSTRUCTIONS

POWER INPUT

GRAY LEADS: POWER INPUT 12 OR 24 VOLTS AC OR DC, NON-POLARIZED
CURRENT DRAW: 60 MA. MAX.

SWITCH ILLUMINATION

LEDS 12 VOLTS DC, FOR 24 VOLT OPERATION USE ENCLOSED RESISTOR IN SERIES WITH ONE SIDE OF LED.

YELLOW WIRE: POSITIVE SIDE OF LED

BLACK WIRE: NEGATIVE SIDE OF LED

MOMENTARY OUTPUT

CONTACTS RATED 2A. @ 35 VDC

WHITE LEAD: COMMON CONTACT

WHITE/RED LEAD: NORMALLY-OPEN CONTACT

RED LEAD: NORMALLY-CLOSED CONTACT

TIMED OUTPUT

CONTACTS RATED 2A, @35 VDC

GREEN LEAD: COMMON CONTACT

VIOLET LEAD: NORMALLY-OPEN CONTACT

BLUE LEAD: NORMALLY-CLOSED CONTACT

TIME ADJUSTMENT

TIME RANGE: TWO TO 45 SECONDS

ROTATE POT TO MAX FOR MAXIMUM DELAY

TIMER WILL ACTIVATE WHEN **"PUSH TO EXIT"** SWITCH IS DEPRESSED.
SUBSEQUENT DEPRESSIONS OF THE SWITCH WILL RE-START THE TIMER.



ALARM CONTROLS CORPORATION

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

PH: 1 800 645-5538 1 631 586-4220 FAX ; 1 631 586-6500

WWW.ALARMCONTROLS.COM EMAIL: INFO@ALARMCONTROLS.COM