RCI Electric Strikes





12C Compact Strike

A versatile strike suitable for all types of door frames. 1-13/16"W \times 2-3/4"H \times 1-1/8"D (46mm \times 70mm \times 28mm)



Energy 90mA 12VDC



Strength¹ 1,100lbf Static 44ft-lb Dynamic



Warranty 1 Year Limited Warranty



Mode Fail-Secure

¹Internal testing

- Quick and easy to install
- · Ideal for wooden, steel & aluminum frames
- · Non-handed
- Versatile, compact design
- · Replaces standard, non-electrified T-strikes
- · Maintains integrity and strength of the door frame
- · Brushed Chrome (26D)

How To Order

12C x 26D

VR165 Vertical Rod Strike

Accommodates 5/8" (16mm) roller latch. Designed for use with vertical rod exit devices with roller latch.



Energy 450mA¹ Field-Selectable 12/24VDC & 12-24VAC



Strength 1,500lbf Static 70 Dynamic ft-lb



Warranty 5 Year Limited Warranty



Mode Fail-Secure



Endurance 250,000 Cycles

¹Max at 12VDC

- Accommodates 5/8" (16mm) roller latch
- · Heavy-duty, surface mounted strike
- · High grade stainless steel ensures superior keeper strength
- Ensure proper latch alignment up to 1/4" (6.4mm) adjustment to compensate for door and frame misalignments
- · Door stop adjustment for different rail thicknesses
- Horizontal solenoid prevents manipulation from vibration
- Conventional keeper design (one moving part) promotes even load distribution
- · Lockdown tabs for secure mount
- · Non-handed
- HEX socket head cap screws for added support and tamper-resistance
- Plug-in wire connector
- Installation tool included (HEX key)
- · Brushed Stainless Steel (32D) finish
- \bullet UL 1034 burglary-resistant Listed
- UL 294 Listed for access Control Unit Accessory (6th Edition)

• Patent #: US 7,722,097

• Patent #: Canadian 2,597,916

How To Order

VR165 x 32D

Example: VR165 x 32D